



PVC SG-5

SG-5 PVC resin is a medium molecular weight resin, general purpose, vinyl suspension resin designed primarily for the extrusion of rigid products where consistent particle size distribution, low contamination and residual VCM levels are important. This resin has good color and thermal stability.

Suggested Applications

SG-5 is typically used in rigid PVC compounds which can be processed through the modern high output, multi-screw extruders to produce pipe, siding, window, door, and fence lineals.

| Parameter | Grade | |
|--|-----------|------|
| Standard: GB/T 5761-2018 | SG-5 | |
| Value | 65-67 | |
| Polymerization Degree | 1000+/-50 | |
| Number of Impurity Particles(<=) | 16 | |
| Volatile Content (incl. water)(%<=) | 0.29 | |
| Apparent Density(g/ml) | 0.52 | |
| Particle Size | 0.25mm | 0.2 |
| | 0.063mm | 99.6 |
| Number of Fish Eye(/400cm ²)(<=) | 14 | |
| Plasticizer Absorption of 100g Resin(>=) | 26 | |
| Whiteness(160°C, 10 min)/% | 84 | |
| VCM Residue PPM(<=) | 3 | |

All statements, information and data given herein are believed to be accurate and reliable but are presented without guaranty, warranty, or responsibility of any kind, expressed or implied. Statements or suggestions concerning possible use of our products are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe any patent. The user should not assume that all safety measures are indicated or that other measures may not be required.